

CROWN


SP 3500 SERIES

Profile Sheet

Four-Point Stockpicker
SP 3570F Model



SP 3570F Model

				Imperial				Metric					
General Information	1	Manufacturer		Crown Equipment Corporation									
	2	Model		SP 3570F									
	3	Load Capacity*	24" (600 mm) Load Center to 276" (7010 mm)	lb	kg	3000				1360			
	4	Load Center	Platform face to load CG	in	mm	24				600			
	5	Power	Electric	24 Volts									
	6	Operator Type	Stand-up Rider	Stockpicker									
	7	Tire Type	Load / Drive / Caster	Poly / Poly / Poly									
	8	Wheels	Load / Drive / Caster	2 / 1 / 1									
		Mast Type	Triple-telescopic	TT									
Dimensions	10	Lift Height	(LH)	in	mm	210	5335	240	6095	276	7010	294	7470
						312	7925	330	8380	348	8840	366	9295
		Free Lift	With LBR	in	mm	8	205	20	510	32	815	38	965
						44	1120	56	1425	62	1575	68	1730
	11	Collapsed Height		in	mm	95	2415	107	2720	119	3025	125	3175
						131	3330	143	3630	149	3785	155	3935
	12	Extended Height	(EH)	in	mm	298	7570	328	8330	364	9250	382	9705
						400	10160	418	10620	436	11075	454	11535
		Truck Weight	Without Battery	lb	kg	6295	2855	6490	2944	6887	3124	7008	3179
						7101	3221	7231	3280	7324	3322	7417	3364
	13	Head Length		in	mm	75.6				1920			
	14	Forks	Standard L x W x T	in	mm	36 x 4 x 2				914 x 100 x 50			
			Optional Lengths	in	mm	30, 39, 42, 45, 48, 54, 60, 72, 84				762, 990, 1067, 1143, 1219, 1372, 1524, 1829, 2134			
	15	Wheelbase		in	mm	87.5				2222			
	16	Turning Radius		in	mm	98.5				2502			
17	Aisle Guide Wheel Range		in	mm	49.5 to 77.5 (11.5 to 15.5 Greater than inside straddle in .25" increments)				1260 to 1970 (292 to 394 Greater than inside straddle in 6 mm increments)				
18	Straddle Width	Inside Straddle	in	mm	38 to 63 in 1" increments				970 to 1600 in 25 mm increments				
		Outside Straddle	in	mm	Add 11				Add 279				
19	Operator Compartment Width		in	mm	48 Standard; 42, 54, 60 and 64 Optional				1220 Standard; 1070, 1370, 1525 and 1625 Optional				
Battery	Battery		Type		Lead Acid				Lead Acid				
			Min Weight	lb	kg	1520				690			
			Max Amp		amp	1085				1085			
			Max Size L X W X H	in	mm	36.25 x 14.25 x 31				920 x 360 x 790			

* Contact factory. Capacity depends on maximum lift height, straddle width, load center and fork length.



Crown Equipment Corporation

New Bremen, Ohio 45869 USA

Tel 419-629-2311

Fax 419-629-3796

crown.com

You can count on Crown to build lift trucks designed for safe operation, but that's only part of the safety equation. Crown encourages safe operating practices through ongoing operator training, safety-focused supervision, maintenance and a safe working environment. Go to crown.com and view our safety section to learn more.

Because Crown is continually improving its products, specifications are subject to change without notice.

Crown, the Crown logo, the color beige, the Momentum symbol, Access 1 2 3, InfoLink, InfoLink for Windows, InfoPoint and Work Assist are trademarks of Crown Equipment Corporation. Other trademarks are property of their owners.

Copyright 2010-2014 Crown Equipment Corporation
SF18482 Rev. 02/14
Printed in U.S.A.