

CROWN



RR 5700 Series

Profile Sheet

RR 5700 Series

		Crown Equipment Corporation						
		RR 5715-35	RR 5715-40	RR 5725-35	RR 5725-45			
General Information	1	Manufacturer						
	2	Model	RR 5715-35	RR 5715-40	RR 5725-35	RR 5725-45		
	3	Load Capacity*	Max	3500	4000	3500	4500	
	4	Load Center	Fork Face to Load CG	in	24	24	24	24
	5	Power						
	6	Operator Type	Reach	Stand	Stand	Stand	Stand	
	7	Tire Type	Load/Caster/Drive	Poly / Poly / Poly				
	8	Wheels (x = driven)	Load/Power Unit	4 / 2 (1x)				
Dimensions		Mast Type	High Visibility					
	9	Lift Height	in	See Mast Chart				
	10	Guard Height	in	See Mast Chart				
	13	Forks	Standard L x W x T	36 x 4 x 1.75				
			Optional Lengths	30, 39, 42, 45, 48				
	14	Carriage	Tilt F°/B°	degree	3 / 4			
	15	Headlength**	Comp't "B"	in	49.28	49.28	49.28	na
			Comp't "C"	in	51.28	51.28	51.28	52.91
			Comp't "D"	in	na	na	na	54.66
			Comp't "E"	in	na	na	na	57.28
17	Overall Collapsed Height	in	See Mast Chart					
18	Overall Extended Height	in	See Mast Chart					
20	Inside Straddle Width	In 1" increments	in	34 - 50				
Chassis	37	Tires	Size - Drive/Caster	in	13 x 5.5 / 8 x 4			
	38	Wheelbase (Standard Wheel)	Comp't "B"	in	54.24	54.24	54.24	na
			Comp't "C"	in	56.24	56.24	56.24	59.57
			Comp't "D"	in	na	na	na	61.32
			Comp't "E"	in	na	na	na	63.95
	39	Suspension	Drive	Articulated				
			Caster	Articulated, Swivel				
42	Brakes	Drive	Elec Release / Mech Applied					
		Caster	None					
		Parking	Elec Release/Mech Applied					
Battery		Battery Removal	Both Sides					
	45	Type	Lead Acid					
	46	Min Weight/Max Amp	Comp't "B"	lb/amp	1600 / 1085	1600 / 1085	1600 / 775	na
			Comp't "C"	lb/amp	1880 / 1020	1880 / 1020	1880 / 930	2000 / 930
			Comp't "D"	lb/amp	na	na	na	2280 / 1085
			Comp't "E"	lb/amp	na	na	na	2600 / 1240
		Max Battery Size	Comp't "B"	in	14.25x38.38x31	14.25x38.38x31	14.25x38.38x31	na
Comp't "C"			in	16.25x38.38x31	16.25x38.38x31	16.25x38.38x31	16.25x38.38x31	
Comp't "D"			in	na	na	na	18.00x38.69x31	
Comp't "E"			in	na	na	na	20.75x38.69x31	

* Contact factory. Capacity may be subject to derating at height.

** Add 2" with optional side shift.

RR 5700 Series

Models RR 5715-35, 5715-40, 5725-35 and 5725-45				TT					
Mast	9	Lift Height (RR 5715-35 and -40, 270" Max)		198"	210"	240"	270"	300"	
		Free Lift*		41	47	59	71	83	
	10	Guard Height		89	95	95	95	95	
		17	Overall Collapsed Height		89	95	107	119	131
			18	Overall Extended Height*		246	258	288	318
				Minimum Straddle OD		42	42	42	42
Weight	Truck Weight w/o Battery		Battery Compartment						
	RR 5715-35	"B"	lb	5330	5416	5675	na	na	
		RR 5715-40	"C"	lb	5374	5460	5719	5962	na
	RR 5725-35	"B"	lb	5408	5494	5753	na	na	
		"C"	lb	5452	5538	5797	6040	6212	
	RR 5725-45	"C"	lb	5836	5945	6258	6548	7055	
		"D"	lb	5878	5987	6300	6590	7097	
		"E"	lb	5933	6042	6355	6645	7152	

Model RR 5725-45				TT				
Mast	9	Lift Height		321"	341"	366"	400"	
		Free Lift*		92	101	112	124	
	10	Guard Height		95	95	95	95	
		17	Overall Collapsed Height		140	149	160	172
			18	Overall Extended Height*		369	389	414
				Minimum Straddle OD		42	49	50
Weight	Truck Weight w/o Battery		Battery Compartment					
	RR 5725-45	"C"	lb	7231	na	na	na	
		"D"	lb	7273	7524	na	na	
		"E"	lb	7328	7579	7795	8029	

* With load backrest.

Note: Above 321", 6" high load wheel standard.



Crown Equipment Corporation
 New Bremen, Ohio 45869 USA
Tel 419-629-2311
Fax 419-629-3796
 crown.com

You can count on Crown to build lift trucks designed for safe operation, but that's only part of the safety equation. Crown encourages safe operating practices through ongoing operator training, safety-focused supervision, maintenance and a safe working environment. Go to crown.com and view our safety section to learn more.

Because Crown is continually improving its products, specifications are subject to change without notice.

Crown, the Crown logo, the color beige, the Momentum mark, Access 1 2 3, InfoPoint, InfoLink, ThermoAssist, OnTrac and Work Assist are trademarks of Crown Equipment Corporation.

Copyright 2009 Crown Equipment Corporation
 SF18380 7/09
 Printed in U.S.A.