



C-D

8,000-12,000 lb Capacity
IC Pneumatic Tire

Specifications





CD35S-9



C-D Series

IC Pneumatic Tire



C-D Series

Specifications

				Imperial	Metric	Imperial	Metric
General	1.2	Model		CD35S-9		CD40S-9	
	1.3	Power Type		Diesel			
	1.4	Operator Type		Seated			
	1.5	Load Capacity	lb kg	8,000	3500	9,000	4000
	1.6	Load Center	Fork Face to Load CG in mm	24	600	24	600
	1.8	Load Distance	Center of Wheel to Fork Face in mm	22	560	22	560
Weight	1.9	Wheelbase	in mm	79.5	2015	79.5	2015
	2.1	Service Weight	lb kg	12,775	5795	13,450	6100
	2.2	Axle Load	Loaded, Front/Rear lb kg	18,495/1,995	8390/905	2,095/2,170	9115/985
	2.3		Unloaded, Front/Rear lb kg	4,970/7,805	2255/3540	5,345/8,105	2425/3675
Tires	3.1	Tire Type		Pneumatic			
	3.2	Tire Size	Front	8.25x15-14PR/7.50x16-12PR		300x15-18PR/7.50x16-12PR	
	3.3		Rear	7.00x12-12PR			
	3.5	Wheels	Number Front / Rear x = driven	x 2 / 2			
	3.6	Track Width	Front in mm	44.9/50.8	1140/1290	45.5/50.8	1155/1290
	3.7		Rear in mm	43.9	1115	43.9	1115
Dimensions	4.1	Mast	Tilt, Forward / Backward deg	See Mast Chart			
	4.2		Collapsed Height in mm				
	4.3		Free Lift in mm				
	4.4		Fork Height in mm				
	4.5		Extended Height in mm				
	4.7	Height of Overhead Guard, Cabin	OHG/Cabin in mm	87.6	2225	87.8	2230
	4.8	Seat Height	in mm	48	1220	48.2	1225
	4.20	Head Length	Length to Fork Face in mm	116.3	2995	118.1	3000
	4.21	Overall Width	in mm	53.9	1370	57.3	1455
	4.22	Forks	Thickness x Width x Length in mm	41.3x5.9x2.0	1050x150x50	41.3x5.9x2.0	1050x150x50
	4.23	Fork Carriage	ISO Class Type	III		III	
	4.24		Width in mm	49.2	1250	49.2	1250
	4.31	Ground Clearance	Loaded, Lowest Point in mm	5.9	150	6.3	160
	4.32		Center of Wheelbase in mm	8.1	205	8.1	205
	4.34.1	Working Aisle Width	40in x 48in Cross-ways in mm	175.0	4445	176.8	4488
	4.34.2	(Right Angle Stack)	48in x 40in Cross-ways in mm	181.3	4605	183.0	4648
Performance	4.35	Turning Radius	External in mm	108.5	2755	110.2	2800
	4.36		Internal in mm	31.7	805	31.7	805
	5.1	Travel Speed	Loaded/Empty mph km/h	15/16	24/26	15/16	24/26
	5.2	Lift Speed	Loaded/Empty fpm m/s	109/117	0.56/0.60	107/117	0.55/0.60
	5.3	Lowering Speed	Loaded/Empty fpm m/s	88.5/98.4	0.45/0.50	88.4/98.4	0.45/0.50
	5.5	Draw Bar Pull @1mph/1.6kph	Loaded/Empty lb kg	7,660/-	34075/-	7,540/-	33540/-
	5.6	Max. Draw Bar Pull	Loaded/Empty lb kg	8,430/-	37498/-	8,295/-	36894/-
	5.7	Gradeability @1mph/1.6kph	Loaded/Empty %	38.5/-		34.5/-	
5.8	Max. Gradeability	Loaded/Empty %	43.0/-		38.5/-		
5.10	Brakes	Service Type	Foot/Hydraulic				
5.10.2		Parking Type	Electronic				
Drivetrain	7.1	Manufacturer/Model		HDI (Hyundai Infracore)/DM03V			
	7.2	Power	DIN ISO1585 HP HP/kW	74.0	55.4	74.0	55.4
	7.3	Rated Speed	RPM min-1	2,300			
	7.3.1	Torque	@ 1min. ft-lb@rpm N-m@rpm	265.4 @ 1,400	360 @ 1400	265.4 @ 1,400	360 @ 1400
	7.4	Number of Cylinders/Displacement	# cm³	4	3409	4	3409
	7.10	Battery Voltage/Nominal Capacity	Voltage/Ampere hour V Ah	12	100	12	100
	8.0	Transmission	Type	Auto-shift			
	8.2.1	Number of Speeds	Forward/Reverse	2/2			
Other	10.1	Operating Pressure for Attachments	psi bar	2,320.5	160	2,320.5	160
	10.2	Oil Volume for Attachments	gpm lpm	29.1	110	29.1	110
	10.4	Fuel Tank Capacity	gal l	27.7	105	27.7	105
	10.7	Sound Level @ Driver's Ear	EN 12053 dB(A)	79			

Note: Values listed in the specification sheet have been rounded. Performance may vary due to operation conditions and / or forklift configurations. Products and specifications are subject to change without prior notice.

C-D Series

Specifications

			Imperial		Metric		Imperial		Metric		Imperial		Metric	
			CD45S-9		CD50C-9		CD55C-9							
General	1.2	Model												
	1.3	Power Type			Diesel									
	1.4	Operator Type			Seated									
	1.5	Load Capacity	lb kg		10,000 4500		11,000 5,000		12,000 5500					
	1.6	Load Center	Fork Face to Load CG	in mm	24 600		24 600		24 600					
	1.8	Load Distance	Center of Wheel to Fork Face	in mm	22 560		22.5 570		22.5 570					
Weight	1.9	Wheelbase	in mm		83.3 2115		83.3 2115		83.3 2115					
	2.1	Service Weight	lb kg		14,395 6530		15,280 6930		16,095 7300					
	2.2	Axle Load	Loaded, Front/Rear	lb kg	21,960/2,370 9960/1070		23,745/2,555 10770/1160		25,495/2,720 11565/1235					
	2.3		Unloaded, Front/Rear	lb kg	5,800/8,595 2630/3900		5,855/9,524 2655/4275		5,965/10,130 2705/4595					
Tires	3.1	Tire Type			Pneumatic									
	3.2	Tire Size	Front		300x15-18PR / 7.50x16-12PR									
	3.3		Rear		7.00x12-12PR		7.00x12-14PR		7.00x12-14PR					
	3.5	Wheels	Number Front / Rear	x = driven	x 2 / 2									
	3.6	Track Width	Front	in mm	45.5/50.8 1155/1290		45.5 / 50.8 1155 / 1290		45.5 / 50.8 1155 / 1290					
	3.7		Rear	in mm	43.9 1115		43.9 1115		43.9 1115					
Dimensions	4.1	Mast	Tilt, Forward / Backward	deg										
	4.2		Collapsed Height	in mm										
	4.3		Free Lift	in mm										
	4.4		Fork Height	in mm										
	4.5		Extended Height	in mm										
	4.7	Height of Overhead Guard, Cabin	OHG/Cabin	in mm	87.8 2230		87.8 2230		87.8 2230					
	4.8	Seat Height		in mm	48.2 1225		48.2 1225		48.2 1225					
	4.20	Head Length	Length to Fork Face	in mm	128.4 3260		129.9 3300		131.5 3340					
	4.21	Overall Width		in mm	53.9 1455		57.3 1455		57.3 1455					
	4.22	Forks	Thickness x Width x Length	in mm	47.2x5.9x2.0 1200x150x50		47.2 x5.9x2.0 1200x150x50		47.2 x5.9x2.0 1200x150x50					
	4.23	Fork Carriage	ISO Class	Type	IV		IV		IV					
	4.24		Width	in mm	52.4 1330		52.4 1330		52.4 1330					
	4.31	Ground Clearance	Loaded, Lowest Point	in mm	6.3 160		6.3 160		6.3 160					
	4.32		Center of Wheelbase	in mm	8.1 205		8.1 205		8.1 205					
	4.34.1	Working Aisle Width (Right Angle Stack)	40in x 48in Cross-ways	in mm	178.7 4539		179.5 4559		180.7 4590					
	4.34.2		48in x 40in Cross-ways	in mm	189.4 4810		190.6 4840		187.0 4750					
	4.35	Turning Radius	External	in mm	112.2 2850		113 2870		114.2 2900					
	4.36		Internal	in mm	32.3 820		32.3 820		32.3 820					
Performance	5.1	Travel Speed	Loaded/Empty	mph km/h	15/16 24/26		15/16 24/26		15/16 24/26					
	5.2	Lift Speed	Loaded/Empty	fpm m/s	105/117 0.54/0.60		103/117 0.53/0.60		101/117 0.52/0.60					
	5.3	Lowering Speed	Loaded/Empty	fpm m/s	88.5/98.4 0.45/0.50		88.5/98.4 0.45/0.50		88.5/98.4 0.45/0.50					
	5.5	Draw Bar Pull @1mph/1.6kph	Loaded/Empty	lb kg	7,545/- 33564/-		7,505/- 33390/-		7,455/- 33170/-					
	5.6	Max. Draw Bar Pull	Loaded/Empty	lb kg	8,310/- 36970/-		8,275/- 36816/-		8,225/- 36595/-					
	5.7	Gradeability @1mph/1.6kph	Loaded/Empty	%	31.5/-		28.5/-		26.0/-					
	5.8	Max. Gradeability	Loaded/Empty	%	35.0/-		31.5/-		29.0/-					
	5.10	Brakes	Service	Type	Foot/Hydraulic									
	5.10.2		Parking	Type	Electronic									
Drivetrain	7.1	Manufacturer/Model			HDI (Hyundai Infracore)/DM03V									
	7.2	Power	DIN ISO1585	HP kW	74.0 55.4		74.0 55.4		74.0 55.4					
	7.3	Rated Speed	RPM	min-1	2,300									
	7.3.1	Torque	@ 1min.	ft-lb@rpm N-m@rpm	265.4 @ 1400 360 @ 1400		265.4 @ 1400 360 @ 1400		265.4 @ 1400 360 @ 1400					
	7.4	Number of Cylinders/Displacement		# cm³	4 3409		4 3409		4 3409					
	7.10	Battery Voltage/Nominal Capacity	Voltage/Ampere hour	V Ah	12 100		12 100		12 100					
	8.0	Transmission			Type		Auto-shift							
	8.2.1	Number of Speeds	Forward/Reverse		2/2									
Other	10.1	Operating Pressure for Attachments		psi bar	2,320.5 160		2,320.5 160		2,320.5 160					
	10.2	Oil Volume for Attachments		gpm lpm	29.1 110		29.1 110		29.1 110					
	10.4	Fuel Tank Capacity		gal l	31.4 119		31.4 119		31.4 119					
	10.7	Sound Level @ Driver's Ear	EN 12053	dB(A)	79									

Note: Values listed in the specification sheet have been rounded. Performance may vary due to operation conditions and / or forklift configurations. Products and specifications are subject to change without prior notice.

C-D Series

Specifications

Mast Chart CD35S-9 & CD40S-9

Mast Type	Maximum Fork Height		Collapsed Height		*Extended Height		*Free Lift	
	mm	in	mm	in	mm	in	mm	in
TL	3000	118	2235	88	4260	168	155	6
	3300	130	2385	94	4560	180	155	6
	3650	144	2560	101	4910	193	155	6
	4000	157	2870	113	5260	207	155	6
	4250	167	2010	119	5510	217	155	6
	4850	191	3460	136	6110	241	155	6
	5250	207	3660	144	6510	256	155	6
TF	3000	118	2215	87	4235	167	1448	57
TT	4000	157	2095	82	5260	207	1321	52
	4250	167	2185	86	5525	218	1422	56
	4500	177	2270	89	5780	228	1524	60
	4700	185	2335	92	5975	235	1575	62
	5150	202	2485	98	5425	253	1727	68
	5600	220	2635	104	6875	271	1880	74
	6050	238	2785	110	7325	288	2007	79
	6500	256	2935	116	7775	306	2184	86
	7000	276	3115	123	8275	326	2362	93

* With Load Backrest

Mast Chart CD45S-9

Mast Type	Maximum Fork Height		Collapsed Height		*Extended Height		*Free Lift	
	mm	in	mm	in	mm	in	mm	in
TL	3000	118	2235	88	4260	168	155	6
	3300	130	2385	94	4560	180	155	6
	3650	144	2560	101	4910	193	155	6
	4000	157	2870	113	5260	207	155	6
	4250	167	2997	118	5510	217	155	6
	4850	191	3460	136	6110	241	155	6
	5250	207	3660	144	6510	256	155	6
TF	3000	118	2200	87	4385	173	1448	57
TT	3700	146	1985	78	5115	201	1143	45
	4000	157	2080	82	5410	213	1245	49
	4250	167	2185	86	5675	223	1346	53
	4500	177	2260	89	5930	233	1422	56
	4700	185	2337	92	6125	241	1499	59
	5150	203	2490	98	6575	259	1651	65
	5600	220	2642	104	7025	277	1803	71
	6050	238	2794	110	7475	294	1956	77
	6500	256	2920	115	7925	312	2083	82

Mast Chart CD50C-9 & CD55C-9

Mast Type	Maximum Fork Height		Collapsed Height		*Extended Height		*Free Lift	
	mm	in	mm	in	mm	in	mm	in
TL	2750	108	2235	88	4160	164	155	6
	3050	120	2388	94	4460	176	155	6
	3400	134	2565	101	4810	189	155	6
	3750	147	2870	113	5160	203	155	6
	4000	157	2995	118	5410	213	155	6
	4600	181	3445	136	6010	237	155	6
	5000	197	3645	144	6410	252	155	6
	5500	217	3895	153	6910	272	155	6
	5800	228	4045	159	7210	284	155	6
TF	2875	113	2200	87	4260	168	1245	49
TT	3575	141	1985	78	4990	196	1041	41
	3875	152	2080	82	5285	208	1118	44
	4125	162	2184	86	5550	219	1219	48
	4575	180	2337	92	6000	236	1372	54
	5025	197	2489	98	6450	254	1524	60
	5325	210	2570	101	6750	266	1626	64
	5475	215	2642	104	6900	272	1676	66
	5925	233	2770	110	7350	289	1829	72

* With Load Backrest

Standard Features

- HDI (Hyundai Infracore) 4 cylinder turbo Diesel engine compliant to current EPA Tier IV standards
- 2 Speed Powershift transmission with Autoshift feature
- Cast Iron one piece axle housing
- Oil-cooled Disc Brakes – Fully enclosed
- Rugged steer axle with large King Pins and tapered roller bearings
- Lift and Tilt locking hydraulic valve
- Carriage Side Thrust rollers
- Dual Element air cleaner with high air intake
- Operator design features
 - Wide Spacious floorboard
 - Tilt and Telescopic Steering Column
 - Suspension seat (vinyl or cloth) with high visibility seat belt
 - OSS Operator Sensing System
 - Park brake alarm and seat belt indicator
 - Rear travel handle with horn
 - Low front cowl/dash optimizes site lines
 - Clear view overhead guard and mast design
 - Large Dual Mirrors
 - Front LED Work Lights
 - 5" Color Display
 - Easy to read gauges monitor engine oil pressure, engine coolant, transmission temp, brake oil level and mast interlock
 - Spinner Knob

Optional Equipment

- Tilt Position Assist (auto-tilt leveling)
- Adjustable Top Speed Control
- Hydraulic Lift Circuit Accumulators
- Pre-Cleaner Air Intake
- Operator Fans
- Panoramic Mirror
- Fuel Sensor Light / Alarm
- 12 Volt auxiliary supply
- Fire Extinguisher
- Combo Lights with Turn signals
- Overhead guard covers
- Enclosed Cab Options - With Heat and Air Conditioning
- Solid Pneumatic (super-elastic) Tires
- Various Light Packages
- Static Strap
- InfoLink® Ready
- Quick Disconnect Attachment Couplings
- Lifting Eyes
- Fuel Cap with Key Lock
- UL DS rating
- 4th Function Lock out (for clamping attachments)
- Vented Side Panels
- Weight Scales

Warning Device Options

Audible or Visual Alerts

Safety considerations and dangers associated with audible travel alarms and lights include:

- Multiple alarms and/or lights can cause confusion.
- Workers ignore the alarms and/or lights after day-in and day-out exposure.
- Operator may transfer the responsibility for “looking out” to the pedestrians.
- Annoys operators and pedestrians.

Other Options Available

Contact your local Crown dealer for additional options.

Dimensions and performance data given may vary due to manufacturing tolerances. Performance is based on an average size vehicle and is affected by weight, condition of vehicle, how it is equipped and the conditions of the operating area. Products and specifications are subject to change without notice.

Note: Mast Specifications and Rated Capacities are based on a standard chassis with pneumatic tire and without side shifter.



crown.com

You can count on Crown to sell lift trucks designed for safe operation, but that's only part of the safety equation. Crown encourages safe operating practices through ongoing operator training, safety-focused supervision, maintenance and a safe working environment. Go to crown.com and view our safety section to learn more.

Because Crown is continually improving its products, specifications are subject to change without notice.

Crown, the Crown logo, the color beige, the Momentum symbol, and InfoLink are trademarks of Crown Equipment Corporation in the United States and other countries.

Copyright 2018-2026 Crown Equipment Corporation
SF19902 Rev. 08-26